



Dual N-Channel Enhancement Mode Field Effect Transistor
FEATURES

- $V_{DS}=60V, I_D=3.5A, R_{DS(ON)} \leq 90m\Omega @ V_{GS}=10V$
- Low on-resistance and low gate charge
- For synchronous rectifier applications
- Surface Mount device


SOP-8

MECHANICAL DATA

- Case: SOP-8
- Case Material: Molded Plastic. UL flammability
- Classification Rating: 94V-0
- Weight: 0.3 grams (approximate)

MAXIMUM RATINGS ($T_A = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	10Sec	Steady state	Unit
Drain-source voltage	V_{DS}	60		V
Gate-source voltage	V_{GS}	± 20		V
Continuous drain current	I_D	$T_A = 25^\circ C$	3.5	A
		$T_A = 70^\circ C$	2.8	A
Pulsed drain current	I_{DM}	20		A
Power dissipation	P_D	$T_A = 25^\circ C$	2	W
		$T_A = 70^\circ C$	1.3	W
Avalanche Current	I_{AR}	8		A
Repetitive avalanche energy 0.3mH	E_{AR}	9.6		mJ
Thermal resistance from Junction to ambient	$R_{\theta JA}$	90		$^\circ C/W$
Thermal resistance from Junction to Lead	$R_{\theta JL}$	40		$^\circ C/W$
Junction temperature	T_J	150		$^\circ C$
Storage temperature	T_{STG}	-55 ~ +150		$^\circ C$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Drain-Source breakdown voltage	$V_{(BR)DSS}^*$	60			V	$V_{GS}=0V, I_D=250\mu A$
Zero gate voltage drain current	I_{DSS}^*			1	μA	$V_{DS}=60V, V_{GS}=0V$
Gate-body leakage current	I_{GSS}^*			± 100	nA	$V_{DS}=0V, V_{GS}=\pm 20V$
Gate-threshold voltage	$V_{GS(th)}^*$	1.7	2.3	2.6	V	$V_{DS}=V_{GS}, I_D=250\mu A$
On-State Drain Current	$I_{D(ON)}$	20			A	$V_{DS}=5V, V_{GS}=10V$
Drain-source on-resistance	$R_{DS(ON)}^*$		79	90	m Ω	$V_{GS}=10V, I_D=3A,$
			146	159	m Ω	$V_{GS}=10V, I_D=3A, T_J=125^\circ C$
			86	105	m Ω	$V_{GS}=4.5V, I_D=2A$
Forward transconductance	g_{FS}		15		S	$V_{DS}=5V, I_D=3A$
Diode forward voltage	V_{SD}		0.8	1	V	$I_S=1A, V_{GS}=0V$
Diode forward current	I_S			2.5	A	
Input capacitance	C_{iss}		372	450	pF	$V_{DS}=30V, V_{GS}=0V, f=1MHz$
Output capacitance	C_{oss}		31		pF	
Reverse transfer capacitance	C_{rss}		17		pF	
Gate resistance	R_g		1.7	2.6	Ω	$V_{DS}=0V, V_{GS}=0V, f=1MHz$
Total gate charge	Q_g		3.6		nC	$V_{GS}=4.5V, V_{DS}=30V, I_D=3A$
			7.1	9.2	nC	
Gate-source charge	Q_{gs}		1		nC	$V_{GS}=10V, V_{DS}=30V, I_D=3A$
Gate-drain charge	Q_{gd}		2		nC	
Turn-on delay time	$t_{d(on)}$		4.1	5.3	nS	$V_{GS}=10V, V_{DS}=30V,$ $R_{GEN}=3\Omega, R_L=10\Omega$
Turn-on rise time	t_r		2.1		nS	
Turn-off delay time	$t_{d(off)}$		15		nS	
Turn-off fall time	t_f		2.1		nS	
Body Diode Reverse Recovery Time	t_{rr}		23.4	29	nS	$I_F=3A, di/dt=100A/\mu s$
Body Diode Reverse Recovery Charge	Q_{rr}		23.2		nC	$I_F=3A, di/dt=100A/\mu s$

*Pulse test ; Pulse width $\leq 300\mu s$, Duty cycle $\leq 0.5\%$.

Dual N-Channel Enhancement Mode Field Effect Transistor

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Dual N-Channel Enhancement Mode Field Effect Transistor

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)





Figure 11: Normalized Maximum Transient Thermal Impedance


Dual N-Channel Enhancement Mode Field Effect Transistor

SOP-8 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.800	5.000	0.189	0.197
e	1.270(BSC)		0.050 (BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

SOP-8 Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters
2. General tolerance: ±0.05mm
3. The pad layout is for reference purposes only

Dual N-Channel Enhancement Mode Field Effect Transistor


SOP-8 Tape and Reel

SOP-8 Embossed Carrier Tape




DIMENSIONS ARE IN MILLIMETER										
TYPE	A	B	C	d	E	F	P0	P	P1	W
SOP-8	6.40	5.40	2.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00
TOLERANCE	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1

SOP-8 Tape Leader and Trailer



SOP-8 Reel



DIMENSIONS ARE IN MILLIMETER								
REEL OPTION	D	D1	D2	G	H	I	W1	W2
13" DIA	Ø330.00	100.00	13.00	R151.00	R56.00	R6.50	12.40	17.60
TOLERANCE	±2	±1	±1	±1	±1	±1	±1	±1