



FEATURES

- UL Recognized Component
- High surge current capability
- Ideal for Printed Circuit Board
- Plastic Package - UL Flammability Classification 94V-0


MECHANICAL DATA

- Case: Transfer Molded Epoxy
- Mounting Position: Any
- Terminals: Plated leads solderable per MTL-STD-750, Method 2026



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%

Characteristic	Symbol	MB 05M	MB 1M	MB 2M	MB 4M	MB 6M	MB 8M	MB 10M	Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Average Rectified Output Current @ $T_A = 40^\circ C$	$I_{F(AV)}$	0.8							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30							A
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t	5.0							A ² s
Forward Voltage per element @ $I_F = 0.8 A$	V_{FM}	1.0							V
Peak Reverse Current At Rated DC Blocking Voltage @ $T_A = 25^\circ C$ @ $T_A = 125^\circ C$	I_{RM}	5.0 500							μA
Typical Junction Capacitance per leg (Note 1)	C_j	13							pF
Typical Thermal Resistance per leg (Note 2)	$R_{\theta JA}$ $R_{\theta JL}$	70 20							$^\circ C/W$
Operating and Storage Temperature Range	T_j, T_{STG}	-55 to +150							$^\circ C$

Notes: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts
2. On aluminum substrate P.C.B. with an area of 0.8" x 0.8" (20 x 20mm) mounted on 0.05 x 0.05" (1.3 x 1.3mm) solder pad

Typical Characteristics

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL FORWARD CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

